




Model Name	System	09K	12K	18K	24K
	Outdoor	ASH109CRAWA	ASH112CRAWA	ASH118CRDWA	ASH124CRDWA
	Indoor	ASYW09CRAWA	ASYW12CRAWA	ASYW18CRDWA	ASYW24CRDWA
Cooling	Rated Capacity Btu/hr	9,000	12,000	17,800	22,600
	Capacity Range Btu/hr	3,800-12,000	4,100-12,500	5,000-19,000	6,500-26,000
	Rated Power Input W	810	1,200	1,650	2,150
	SEER	18	18	18	18
	EER	10.5	10.0	10.0	10.0
	Moisture Removal Pt./h	2.50	3.40	4.20	5.90
Heating	Rated Heating Capacity 47°F Btu/hr	10,000	12,000	18,700	26,000
	Heating Capacity Range Btu/hr	4,100-12,000	4,500-16,000	5,400-22,000	6,800-28,000
	Rated Power Input W	850	1,000	1,700	2,400
	HSPF	11.0	11.0	10.5	10.0
Operating Range	Cooling °F(°C)	14°F-115°F(-10-46°C)	14°F-115°F(-10-46°C)	0°F-115°F(-18-46°C)	0°F-115°F(-18-46°C)
	Heating °F(°C)	-4°F-75°F (-20-24°C)	-4°F-75°F (-20-24°C)	-4°F-75°F (-20-24°C)	-4°F-75°F (-20-24°C)
Power Supply	Voltage, Cycle, Phase V/Hz/-	115/60/1	115/60/1	208-230/60/1	208-230/60/1
Outdoor Unit	Compressor Type	DC Inverter Driven Rotary			
	Maximum Fuse Size A	20	20	20	25
	Minimum Circuit Amp A	18	18	17	19
	Outdoor Noise Level dB	47	50	56	53
	Dimension: Height in (mm)	21 1/4(540)	21 1/4(540)	27 7/16 (697)	30 (762)
	Dimension: Width in (mm)	30 11/16(780)	30 11/16(780)	35 (890)	36 3/16 (920)
	Dimension: Depth in (mm)	9 5/8(245)	9 5/8(245)	13 7/8 (353)	15 1/8 (385)
	Weight (Ship/Net)- lbs (kg)	66.2/58.4(30/26.5)	71.7/63.9(32.5/29)	105.8/97.0(48.0/44.0)	121.3/112.5(55.0/51.0)
Indoor Unit	Indoor Sound Level dB (Turbo/High/Med/Low/Quiet)	39/37/33/28/23	39/37/33/28/23	45/43/39/36//33	47/45/40/37/34
	Dimension: Height in (mm)	11 7/16(290)	11 7/16(290)	12 1/2(318)	13 3/16(335)
	Dimension: Width in (mm)	34(864)	34(864)	39 11/16(1008)	44 5/16(1125)
	Dimension: Depth in (mm)	7 7/8(200)	7 7/8(200)	8 7/8(225)	9 7/16(240)
	Weight (Ship/Net)- lbs (kg)	24.7/19.9(11.2/9.0)	24.7/19.9(11.2/9.0)	33.1/26.5(15.0/12.0)	38.6/30.9(17.5/14.0)
Refrigerate Line	Connections	Flare	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2	1/2
	Factory Charge Oz	26.5	35.3	40.6	67.0
	Maximum Line Length Ft / m	66/20	66/20	83/25	83/25
	Maximum Height Ft / m	33/10	33/10	50/15	50/15

**Operating Range (°F):**



**FEATURES & BENEFITS**

**OPTIONAL WIFI CONTROL**



Remotely control ductless system from any smart phone or tablet



**A-PAM DC INVERTER**

Leading compressor technology for maximum comfort and efficiency



**TURBO MODE**

Cools or heats the room quickly




**115V EASY ELECTRIC WIRING**

9k and 12k are 115V, easy electric wiring



**BLUE FIN**

A special coating that whisks away condensate water



**AUTO LOUVER**

Automatically adjusts airflow upward when cooling, or downward when heating



**WARM START**

Ensures the fan will not blow cold air during heating mode startup



**2-WAY PIPING DRAIN**

Allows installer to drain the condensation from either the left or right side, making installation easier



**CHILD LOCK**

Prevents unintended and unsupervised use





Pub No. 64401 05/17/20

Optional Accessories	Description
AWF01RWA	WiFi Module for Highwall Indoor
ACT17CWA	Easy Wired Controller
UCT30RWA (12pk)	Cool Only Remote (Optional)
WK-B	Wired Controller Kit for Wall Mount Type Indoor
QAWB42A	Wind Baffle for Outdoor: ASH109CRAWA and ASH112CRAWA
QAWB37A	Wind Baffle for Outdoor: ASH118CRDWA
QAWB45A	Wind Baffle for Outdoor: ASH124CRDWA

Our continuing commitment to quality products may mean a change in specifications without notice.



Compatible with Google Assistant and Amazon Alexa.



© 2020 GE Appliances, a Haier Company