



Series



Scan this code with your smart device to learn more about Altitude mini-splits.



The ultimate combination of performance and comfort, Altitude Series delivers efficiencies up to 23 SEER and whisper-quiet operation; as low as 23 dB(A). Available Capacities: 9,000 BTU, 12,000 BTU, 15,000 BTU, 18,000 BTU, and 24,000 BTU.

Key Features

DC INVERTER

A-PAM DC INVERTER
Latest high efficiency DC inverter technology



EASY INSTALLATION CLIP
Built-in bracket allows more room to install and service



-15°F HEATING
Low ambient heating down to -15F (-26C)




AUTO LOUVER
Adjusts airflow upward when cooling, or downward when heating



BASE PAN HEATER
Prevents d=accumulating in the outdoor unit in extremely cold temperatures



WARM START
Ensures the fan will not blow cold air during heating mode startup



3-D AIR FLOW
Delivers air vertically and horizontally for even distribution throughout the room



TURBO MODE
Cools or heats the room quickly



BLUE FIN
A hydrophilic aluminum fin, ensures condensing water flows smoothly



QUIET MODE
Minimizes indoor noise while maintaining comfort levels



60+ FT LONG DISTANCE AIR SUPPLY
Optimized fan motor and blower design enables up to 60 feet of air flow



2-WAY PIPING DRAIN
Right or left side drain configuration simplifies installation

SINGLE ZONE MINI-SPLIT SOLUTIONS |



Specifications


Compressor Type:

DC Inverter Driven Rotary

Voltage/Cycle/Phase:

208-230/60/1

Operating Range (°F):



WIFI
Compatible with
WiFi Adapter (QAWF01A)



WIFI
Compatible with
WiFi Adapter (QAWF01A)



WIFI
Compatible with
WiFi Adapter (QAWF01A)



WIFI
Compatible with
WiFi Adapter (QAWF01A)



WIFI
Compatible with
WiFi Adapter (QAWF01A)

		09PR	12PR	15PR	18PR	24PR
	Outdoor Unit	ASH109PRDWA	ASH112PRDWA	ASH115PRDWA	ASH118PRDWA	ASH124PRDWA
	UPC	0-84691-84630-7	0-84691-84633-8	0-84691-84639-0	0-84691-84635-2	0-84691-84637-6
	Indoor Unit	ASYW09PRDWB	ASYW12PRDWB	ASYW15PRDWB	ASYW18PRDWB	ASYW24PRDWB
	UPC	0-84691-84631-4	0-84691-84632-1	0-84691-84638-3	0-84691-84634-5	0-84691-84636-9
Cooling	Rated Capacity Btu/hr	9,000	12,000	15,000	17,000	22,000
	Capacity Range Btu/hr	3,200 - 12,500	3,300 - 15,000	5,400 - 24,000	5,400 - 26,500	6,400 - 30,000
	Rated Power Input W	640	960	1,200	1,390	1,760
	SEER/EER	23.5/14.5	23.0/12.5	21.5/12.5	21.0/12.5	20.0/12.5
	Moisture Removal Pt./hr	3.50	3.90	4.10	4.30	7.00
Heating	Heating Capacity Range Btu/hr	3,800 - 15,600	3,900 - 20,000	4,000 - 26,000	4,000 - 30,000	6,200 - 36,000
	Rated Heating Capacity 47°F Btu/hr	10,000	13,000	16,000	22,000	27,600
	COP	4.4	3.5	3.4	3.4	3.3
	Max. Heating Capacity 17°F Btu/hr	13,000	15,000	17,000	19,000	26,000
	Max. Heating Capacity 5°F Btu/hr	10,000	13,000	16,000	17,000	20,000
	Max Heating Capacity -15°F Btu/hr	6,500	7,500	10,000	12,000	14,000
	Rated Power Input W	680	1,500	1,700	2,100	2,630
	HSPF	10.5	11.0	10.5	10.5	10.5
Outdoor Unit	Maximum Fuse Size A	15	15	20	20	30
	Minimum Circuit Amp A	11.0	11.0	14.0	14.0	20.0
	Outdoor Noise Level dB	54	54	55	55	57
	Dimension: Height in (mm)	23 1/2 (597)	23 1/2 (597)	27 7/16 (697)	27 7/16 (697)	30 (762)
	Dimension: Width in (mm)	30 11/16 (780)	30 11/16 (780)	35 (890)	35 (890)	36 3/16 (920)
	Dimension: Depth in (mm)	11 7/16 (290)	11 7/16 (290)	13 7/8 (353)	13 7/8 (353)	15 1/8 (385)
	ODU Weight Ship/Net - lbs	85/78.5	85/78.5	110.5/100.5	110.5/100.5	141/130
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
	Sound Level dB (Turbo/High/Med/Low/Quiet)	44/40/35/31/23	45/41/36/32/23	48/46/42/36/34	48/46/42/36/34	49/47/42/36/34
	Dimension: Height in (mm)	12 1/4 (310)	12 1/4 (310)	13 1/4 (336)	13 1/4 (336)	13 1/4 (336)
	Dimension: Width in (mm)	35 7/16 (900)	35 7/16 (900)	43 7/8 (1115)	43 7/8 (1115)	43 7/8 (1115)
	Dimension: Depth in (mm)	8 7/16 (215)	8 7/16 (215)	9 9/16 (243)	9 9/16 (243)	9 9/16 (243)
	IDU Weight Ship/Net - lbs	31/25.5	31/25.5	43.5/35.5	43.5/35.5	45.5/38
Refrigerant Lines	Connections	Flare	Flare	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2	1/2	1/2
	Factory Charge Oz	38.8	38.8	52.2	52.2	74.1
	Max Line Length Ft / m	50/15	50/15	83/25	83/25	83/25
	Max Height Ft / m	33/10	33/10	50/15	50/15	50/15

*The Advanced Plus Series will continuously operate at -15°F (-26°C).